



Electrical Test:

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 10M ohm min.
4. Hi-pot:100V DC/10ms
5. Pass through 1440p testing by 100%

REV.	DESCRIPTION		DATE
8	TRANSPARENT DUST COVER		2 pcs
7	45P Black PVC		20 g
6	H.S.T:Ø1.5*16mm Black		2 pcs
5	H.S.T:Ø2.5*10mm Black		10 pcs
4	External shell Hood, Colocr: Golden		2 set
3	Inside Molding:PE		4 g
2	HDMI 19P Male,Solder Type,Insulation Black,Shell Gold Plated		2 pcs
1	UL20276 (7/0.10T*1PR+EAM)*5C+7/0.10T*4C+AB 60%BD OD:7.3MM BLACK		0.5 m
NO	DESCRIPTION		Q'TY UNIT
TOLERANCE		ELEMENT	
INCHES		TITLE: HDMI 30AWG 1.4V Gold Plated 0.5M	
M/M		CUSTOMER : SMT	
DRAWN BY LYNN		CUSTOMER NO.: TRA-007515	
CHECK BY		SCALE NONE	DRAWING NO.: CAA080465
APPD BY		UNIT MM	
		DATE 10.05.17	
		REV. A	1/2