



**Electrical Test:**

- 100%Test(Open ,short ,miss wire)
- Contact Resistance: 2 ohm max.
- Insulation Resistance: 10M ohm min.
- Hi-pot:100V DC/10ms
- Pass through 1440p test by 100%

REV.	DESCRIPTION	DATE
8	TRANSPARENT DUST COVER	2 pcs
7	45P Black PVC	20 g
6	H.S.T:Ø1.5*16mm Black	2 pcs
5	H.S.T:Ø2.5*10mm Black	10 pcs
4	External shell Hood, Colocr: Golden	2 set
3	Inside Molding:PE	4 g
2	HDMI 19P Male,Solder Type,Insulation Black,Shell Gold Plated	2 pcs
1	UL20276 (7/0.10T*1PR+EAM)*5C+7/0.10T*4C+AB 60%BD OD:7.3MM BLACK	2 m
NO	DESCRIPTION	Q'TY UNIT

  

REV.	DESCRIPTION	DATE
	TOLERANCE INCHES M/M	
	.X .015 .30	
	.XX .010 .10	
	.XXX .005 .05	
DRAWN BY	LYNN	
CHECK BY		
APPD BY		

  

TITLE:		CUSTOMER :		REV.
HDMI 30AWG 1.4V Gold Plated 2M		SMT		A
CUSTOMER NO.:		TRA-007517		
SCALE	NONE	DRAWING NO.:	CAA080467	
UNIT	MM			
DATE	10.05.17			1/2