



Electrical Test:

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 10M ohm min.
4. Hi-pot:100V DC/10ms
5. Pass through 1440p test by 100%

REV.	DESCRIPTION		DATE
8	TRANSPARENT DUST COVER		2 pcs
7	45P Black PVC		20 g
6	H.S.T:Ø1.5*16mm Black		2 pcs
5	H.S.T:Ø2.5*10mm Black		10 pcs
4	External shell Hood, Colocr: Golden		2 set
3	Inside Molding:PE		4 g
2	HDMI 19P Male,Solder Type,Insulation Black,Shell Gold Plated		2 pcs
1	UL20276 (7/0.10T*1PR+EAM)*5C+7/0.10T*4C+AB 60%BD OD:7.3MM BLACK		4 m
NO	DESCRIPTION		Q'TY UNIT
TOLERANCE		ELEMENT	
INCHES		M/M	
.X	.015	.30	TITLE: HDMI 30AWG 1.4V Gold Plated 4M
.XX	.010	.10	
.XXX	.005	.05	
DRAWN BY	LYNN		CUSTOMER : SMT
CHECK BY			CUSTOMER NO.: TRA-007519
APPD BY			SCALE NONE
			UNIT MM
			DATE 10.05.17
			DRAWING NO.: CAA080469
			REV. A
			1/2