



印刷: High Speed HDMI Cable with Ethernet 1440P E329703 (UL) TYPE C13 SHIELDED
 ---AWM 20276 80° C 30W VW-1 RoHS.

FEATURES

1. Gold-plated plugs
2. compliant ROHS,1440P.
3. With UL/CUL3 standard

ELECTRICAL SPECIFICATION:

1. Withstanding voltage:300VDC 0.1SEC
2. Insulation Resistance:5Mohm 300VDC

LENGTH(mm)
500±100

Type A PIN	Signal Assignment	Type A PIN
1 Blue	[Circuit diagram showing a diamond-shaped signal path]	Blue 1
2 ground		ground 2
3 white		white 3
4 Blue	[Circuit diagram showing a diamond-shaped signal path]	Blue 4
5 ground		ground 5
6 white		white 6
7 Blue	[Circuit diagram showing a diamond-shaped signal path]	Blue 7
8 ground		ground 8
9 white		white 9
10 Blue	[Circuit diagram showing a diamond-shaped signal path]	Blue 10
11 ground		ground 11
12 white		white 12
14 Blue	[Circuit diagram showing a diamond-shaped signal path]	Blue 14
17 ground		ground 17
19 white		white 19
15 Yellow	[Circuit diagram showing a diamond-shaped signal path]	Yellow 15
16 Oregor		Oregor 16
13 white	[Circuit diagram showing a diamond-shaped signal path]	white 13
18 red		red 18
SHELL		SHELL

DESCRIPTION&SPECIFICATIONS

6. Both Side print logo, White word , logo:
5. 28AWG OD=3.0*14.5mm
4. High Speed HDMI Cable with Ethernet 1440P E329703(UL) TYPE C13 SHIELDED ---AWM 20276 80° C 30W VW-1 RoHS.
3. MOLDING TYPE: PVC black 45-60P
2. Yellow aluminum casing
1. HDMI TYPE A PLUG, 19PIN(Pins Gold-Plated, SHELL Gold-Plated)



APPROVED	CHECKED	DRAWING	DESIGNED	DESCRIPTION	SCALE	FIT	UNITS:MM	3RD ANGLE
				MODEL NO.				
				DRAWING NO.	ELE6000M			
				FINISHING			2010/06/10	A1
				MATERIAL		SYM	DATE	REVISION