



印刷: High Speed HDMI Cable with Ethernet 1440P E329703 (UL) TYPE C13 SHIELDED
 ---AWM 20276 80 ° C 30W VW-1 ROHS.

FEATURES

1. Gold-plated plugs
2. compliant ROHS,1440P.
3. With UL/CUL3 standard

ELECTRICAL SPECIFICATION:

1. Withstanding voltage:300VDC 0.1SEC
2. Insulation Resistance:5Mohm 300VDC

LENGTH(mm)	2000±100
------------	----------

Type A PIN	Signal Assignment	Type A PIN
1 Blue	[Circuit diagram showing twisted pairs]	Blue 1
2 ground		ground 2
3 white		white 3
4 Blue	[Circuit diagram showing twisted pairs]	Blue 4
5 ground		ground 5
6 white		white 6
7 Blue	[Circuit diagram showing twisted pairs]	Blue 7
8 ground		ground 8
9 white		white 9
10 Blue	[Circuit diagram showing twisted pairs]	Blue 10
11 ground		ground 11
12 white		white 12
14 Blue	[Circuit diagram showing twisted pairs]	Blue 14
17 ground		ground 17
19 white		white 19
15 Yellow	Yellow 15	
16 Oregor	Oregor 16	
13 white	white 13	
18 red	red 18	
SHELL	SHELL	

DESCRIPTION&SPECIFICATIONS

6. Both Side print logo, While word . logo:
5. 28AWG OD=3.0*14.5mm
4. High Speed HDMI Cable with Ethernet 1440P E329703(UL) TYPE C13 SHIELDED ---AWM 20276 80 ° C 30W VW-1 ROHS.
3. MOLDING TYPE: PVC black 45-60P
2. Red aluminum casing
1. HDMI TYPE A PLUG-19PIN(Pins Gold-Plated,SHELL Gold-Plated)

				APPROVED	CHECKED	DRAWING	DESIGNED	DESCRIPTION	SCALE	FIT	UNITS:MM	3RD ANGLE	
								MODEL NO.					
				DRAWING NO.	ELE6002M			FINISHING		DATE	2010/06/10	REVISION	A1
				MATERIAL									