



PIN OUT:

P1	COLOR	P2	P1	COLOR	P2
1	RED	1	13	BLACK	13
2	DRAIN	2	14	BROWN	14
3	WHITE	3	15	ORANGE	15
4	RED	4	16	YELLOW	16
5	DRAIN	5	17	RED	17
6	WHITE	6	18	GREEN	18
7	RED	7	19	BLUE	19
8	DRAIN	8		DRAIN	SHELL
9	WHITE	9		SHELL	SHELL
10	RED	10			
11	DRAIN	11			
12	WHITE	12			

NOTES:

ELECTRICAL PROPERTIES:

- 1)100% OPEN.SHORT & MIS-WIRE TEST
- 2)CONTACT RESISTANCE :5 ohm(Max)
- 3)INSULATION RESISTANCE:10M OHM(MIN)
- 4)VOLTAGE:300VDC/10mS, 250VAC/2mA
- 5)ROHS STANDARD

P/N	LENGTH (L)
02.12.HC3049-T24-10M-SW	10000±100
02.12.HC3049-T24-15M-SW	15000±150
02.12.HC3049-T24-20M-SW	20000±200

5	04080032	CAP	FOR HDMI CONNECTOR	2PCS
4	04080004	INNER MOLD	LD-PE	AR
3	04080033	OUTER MOLD	PVC SHORE 85A COLOR: BLACK	AR
2	03060107-1	CONN	HDMI 19P/M INSULATION:BLACK SOLDER TYPE TERMINAL:15U' SHELL:G/F	2PCS
1		CABLE	(2C*24#+2D+AL+MY)*4C+(7C*26#+D+AL)*1C OD:4.2*18MM OD:4.2*18MM CL3 COLOR:BLACK HDMI 1.3	1PCS
NO.	PART NO.	DESCRIPTION	MATERIAL	Q'TY

				CUS NAME:		GN P/N:		CUS	
A		-		02.12.HC3049-T24-10M-SW 02.12.HC3049-T24-15M-SW 02.12.HC3049-T24-20M-SW		015CHH-X-387		015	
GN REV	REASON	DATE	NAME	名称					
DRAW	阳新伟 2007-12-15			HDMI 19P/M TO HDMI 19P/M					
CHECK									
APPROVED									
STANDARD				GN REV	A	UNIT	MM	SHEET: 2 OF 2	

