



Innovation for the Last Mile™

# AC6QS-BVV-NBOX

Series 6, MOCSY™7 coaxial drop cable, quad-shield 60/40% braid, neutral PVC jacket.

## GENERAL SPECIFICATIONS

Braid Coverage 60% + 40% braids  
 Cable Type Series 6  
 Packaging Type Reelex II Box

## CONSTRUCTION MATERIALS

Jacket Material PVC  
 Jacket Color Neutral  
 Shield Materials Bonded APA foil + 60% aluminum braid +  
 Non-bonded APA foil + 40% aluminum braid  
 Dielectric Material Foam PE  
 Inner Conductor Material Copper-clad steel wire

## DIMENSIONS

Cable Length 1000 ft 305 m  
 Diameter over Jacket 0.295 in 7.49 mm  
 Jacket thickness 0.030 in 0.76 mm  
 Diameter over Tape 0.186 in 4.72 mm  
 Diameter over Dielectric 0.177 in 4.49 mm  
 Diameter of Inner Conductor 0.0403 in 1.024 mm  
 Box: Height 20.5 in 520 mm  
 Length 20.5 in 520 mm  
 Width 10.6 in 270 mm  
 Total Weight 39 lb 17.5 kg

## ELECTRICAL SPECIFICATIONS

Operating Frequency Band 5-1525 MHz  
 Impedance 75 Ohms  
 Velocity 85%  
 DC Loop Resistance 36.9 Ω/kft 121 Ω/km  
 Dielectric Strength 1500 V  
 Jacket Spark Test 2500 V

## STANDARD COMPLIANCE

UL/ETL Listings CATV, CM, NEC 830 BM  
 RoHS Compliant  
 SCTE 74 2003 Compliant

Attenuation @ 68°F (20°C)		
MHz	dB/100ft	dB/100m
5	0.58	1.90
55	1.60	5.25
211	3.05	10.00
250	3.30	10.82
270	3.37	11.04
300	3.55	11.64
330	3.74	12.26
350	3.85	12.63
400	4.15	13.61
450	4.40	14.43
500	4.66	15.29
550	4.90	16.08
600	5.10	16.73
750	5.65	18.54
870	6.11	20.04
1000	6.55	21.49
1125	6.95	22.80
1525	8.09	26.54



Specifications subject to change without notice. © 2010 PCT International, Inc.



2260 West Broadway Road | Mesa, AZ 85202 | USA  
 Tel +1.480.813.0925 | Fax +1.480.892.5537 | www.pctcorporate.com